

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 November 2004 (25.11.2004)

PCT

(10) International Publication Number
WO 2004/100736 A1

(51) International Patent Classification⁷: A47G 19/22

(21) International Application Number:
PCT/GB2004/002076

(22) International Filing Date: 14 May 2004 (14.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0311377.6 17 May 2003 (17.05.2003) GB
60/489,511 24 July 2003 (24.07.2003) US

(71) Applicant and

(72) Inventor: CLARE, Claire [GB/GB]; 8 Bowling Green Avenue, Cirencester, Glos GL7 2HB (GB).

(74) Agents: DUNLOP, Brian, Kenneth, Charles et al.; Wynne-Jones, Laine & James, 22 Rodney Road, Cheltenham, Glos. GL50 1JJ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DRINKING VESSEL



(57) Abstract: This invention relates to drinking vessels and in particular a cup, generally indicated at (10), comprising an inner liquid reservoir (11) and an outer splayed wall (12). The angle X between the reservoir (11) and the wall (12) is about 3°. The splayed out wall defines an enlarged based foot print, which both makes the cup stable and contributes to the ability of the cup to restore itself to a vertical position from a significantly tilted position.

WO 2004/100736 A1

Drinking Vessel

This invention relates to drinking vessels.

So called "no spill" drinking cups for toddlers, and indeed the very elderly, have been subject to extensive research and many patents. This type of cup has a lid and a drinking spout and some sort of valving arrangement to prevent liquid coming out of the spout when the cup is inverted or knocked over. As children's dexterity increases, they then tend to progress to an ordinary drinking cup or glass and for the most part these are only distinguished by the make of plastics and varying suitable motifs. The elderly also prefer to be able to use an ordinary drinking vessel for as long as possible. Both the young and the elderly often have a problem putting the drinking vessel back down onto a table with the base parallel to the table top. Instead the edge frequently is the first part of the vessel to touch and if the vessel is released at that point, it will usually fall over and spill its contents.

It has been proposed to provide a cup with a weighted base so that the mass in the base tends to pull the vessel back into a vertical position in the manner of the children's weighted toy clown. However, if such cups are to prevent spilling on the first inclination of the cup, the restoring action has to be rapid and this means that the restoring force is often large causing over compensation, which leads to the liquid sloping violently in the vessel and can lead to spillages in that way. Further the action is likely to encourage young children to deliberately tip the vessel.

From a first aspect the present invention consists in a drinking vessel having an outer wall and an inner liquid reservoir with an open mouth, wherein

the outer wall splays outwardly from the mouth to form a base footprint of greater area than the mouth the arrangement being such that a vertical line extending downwardly from the centre of gravity of the vessel lies within the base footprint when the vessel is inclined with the plane of the base footprint at
5 angles of up to about 50 degrees to the horizontal.

It has been found that by having a base footprint of greater area than the mouth and the centre of gravity arranged as defined above, the vessel not only restores itself to its stable position when misplaced at an angle, on its edge, on a table, there is also limited rebound, so that spills are significantly reduced.

10 Preferably the bottom of the reservoir is flush with the lower edge of the outer wall. This not only maximises the volume that the vessel can contain and increases stability by ensuring that the weight of the liquid adds to the mass adjacent the base footprint, it also increases the sliding friction between the vessel and the surface on which it sits, decreasing the number of accidents that
15 will happen due to the vessel receiving a horizontal force, for example from a flaying arm. The bottom may be patterned to increase the friction.

The reservoir may narrow towards its bottom and, in one arrangement the reservoir and the wall may be constituted by oppositely sensed frusto-cones. The opposite tapering is beneficial, because it enables moulding in a single tool.
20 In a preferred embodiment the vessel is formed as a single integral moulding. The angle between the outer wall and the reservoir may be between 2 and 5 degrees.

The ratio of the area of the mouth to the area of the base may be at least about 3:4.

The vessel may be a cup and may have a handle.

Although angles of up to 50 degrees can conveniently be reached for the angle between the vertical line and the horizontal when the vertical line passes through the base footprint it will be understood that greater angles could be achieved by increasing the area of the base footprint. Equally, for aesthetic reasons, smaller angles may be angles and angles of up to 40 or 45 degrees may provide suitable upper inclinations for certain markets.

From another aspect the invention consists in the drinking vessel having a mouth and the base where the ratio of the area of the mouth to the base is at least about 3:4 and the vessel has an outer divergent wall and an inner liquid reservoir.

Although the invention has been defined above it is to be understood it includes any inventive combination of the features set out above or in the following description.

The invention may be performed in various ways and specific embodiments will now be described, by way of example, with reference to the accompanying drawings, in which:

Figures 1 to 5 are respectfully a side view, an isometric view, a vertical sectional view turned through 90 degrees, a plan view and a view on the arrow A taken on Figure 1.

A cup, generally indicated at 10, comprises an inner liquid reservoir 11 and an outer splayed wall 12. The inner reservoir 11 tapers towards its bottom 13 from a mouth 14 a handle 15 is provided, but the design is equally applicable to handleless drinking vessels. The angle x between the reservoir 11 and wall

12 is about 3 degrees.

It will be understood that the splayed outer wall 12 defines an enlarged base footprint, which not only makes the cup 10 extremely stable against blows to its side wall or handle when it is sitting on a table, it also contributes significantly to the ability of the cup to restore itself to a vertical position from a significantly tilted position. This is because the use of the double wall arrangement in which the reservoir 11 extends downwardly so that the bottom 13 is substantially level with the free edge of the wall 12, means that the centre of gravity of the cup is highly centralised and low within the cup so that a vertical line extending downwardly from the centre of gravity will pass through the base footprint even when the plane of the base footprint is at angles of up about 50 degrees to the horizontal. This means that the cup will restore itself in most situations where the user misplaces it on the table, although it will not prevent deliberate spillage.

In the current embodiment the ratio of the area of the mouth to the area of the base footprint is about 3:4. If the base footprint is increased, the stability will increase, but aesthetically it is believed that this proportion is about the best compromise between looks and functionality.

Claims

1. A drinking vessel having an outer wall and an inner liquid reservoir with an open mouth wherein the outer wall splays outwardly from the mouth to form a base footprint of greater area than the mouth, the arrangement being such that a vertical line extending downwardly from the centre of gravity of the vessel lies within the base footprint when the vessel is inclined with the plane of the base footprint at angles of up to about 50° to the horizontal.
2. A vessel as claimed in claim 1 wherein the bottom of the reservoir is flush with the lower edge of the outer wall.
3. A vessel as claimed in claim 1 or claim 2 wherein the reservoir narrows towards its bottom.
4. A vessel as claimed in claim 1 wherein the walls of the reservoir are constituted by oppositely sensed frusto-cones.
5. A vessel as claimed in claim 1 wherein there is an angle of 2° and 5° between the outer wall and the reservoir.
6. A vessel as claimed in any one of the preceding claims formed as a single integral moulding.
7. A vessel as claimed in any one of the preceding claims wherein the vessel is a cup with a handle.
8. A vessel as claimed in any one of the preceding claims wherein ratio to the area of the mouth to the area of the base is at least about 3:4.
9. A vessel as claimed in any one of the preceding claims wherein the vertical line passes through the base footprint at angles of inclination up to 40° or 45°.

10. A drinking vessel having a mouth and an base wherein the ratio of the area of the mouth to the base is at least about 3:4 and the vessel has an outer divergent wall and an inner liquid reservoir.

5

10

15

20

1/1




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5

INTERNATIONAL SEARCH REPORT

International Application No
P/GB2004/002076

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 A47G19/22		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 A47G B65D		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal, WPI Data		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 867 313 A (PADOVANI PIETRO) 19 September 1989 (1989-09-19) the whole document	1-6, 8-10
X	GB 1 325 230 A (JACOBS S A) 1 August 1973 (1973-08-01) figure 3	1-4, 6, 8-10
X	US 2 493 633 A (MART LEON T) 3 January 1950 (1950-01-03) figure 1	1, 3, 4, 6, 8-10
X	US 3 355 046 A (JOLLY ROSS T) 28 November 1967 (1967-11-28) figure 3	1, 3-5, 7-10
-/-		
<div style="display: flex; justify-content: space-between;"> <input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex. </div>		
<div style="display: flex;"> <div style="flex: 1;"> <p>* Special categories of cited documents:</p> <p>*A* document defining the general state of the art which is not considered to be of particular relevance</p> <p>*E* earlier document but published on or after the international filing date</p> <p>*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>*O* document referring to an oral disclosure, use, exhibition or other means</p> <p>*P* document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="flex: 1;"> <p>*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>*&* document member of the same patent family</p> </div> </div>		
Date of the actual completion of the international search <div style="text-align: center;">22 July 2004</div>		Date of mailing of the international search report <div style="text-align: center;">30/07/2004</div>
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer <div style="text-align: center;">Reichhardt, O</div>

INTERNATIONAL SEARCH REPORT

International Application No
T/GB2004/002076

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 804 281 A (ECKDAHL T H) 16 April 1974 (1974-04-16) figure 2	1,3-5, 8-10
X	US 2 637 182 A (DAVIS G H) 5 May 1953 (1953-05-05) figure 11	1,3,4,6, 8-10
X	US 3 355 045 A (DOUGLAS D) 28 November 1967 (1967-11-28) figure 2	1,3,5, 7-10
X	FR 2 413 286 A (SENECHAL JEAN-PIERRE) 27 July 1979 (1979-07-27) figure 2	1,3-6, 8-10
X	GB 2 355 918 A (PROTECTION PACKAGING LTD) 9 May 2001 (2001-05-09) figure 2	1,3,4, 7-10
X	US 4 412 644 A (LA FEVER WILLIAM C) 1 November 1983 (1983-11-01) figure 3	1,2,7-10
X	US 4 832 212 A (ASKINAZI CLIFFORD) 23 May 1989 (1989-05-23) figure 2	1,2,6, 8-10
X	GB 2 312 611 A (BECK DAVID CHARLES) 5 November 1997 (1997-11-05) the whole document	1,2,6-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

Γ/GB2004/002076

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
✓US 4867313	A	19-09-1989	BE 1000161 A6 CH 673384 A5 DE 3806039 A1 ES 1005325 U1 FR 2611469 A1 GB 2201581 A ,B JP 63277016 A NL 8800522 A PT 86737 A SE 8800729 A	28-06-1988 15-03-1990 15-09-1988 01-11-1988 09-09-1988 07-09-1988 15-11-1988 03-10-1988 30-03-1989 04-09-1988
✓GB 1325230	A	01-08-1973	NONE	
✓US 2493633	A	03-01-1950	NONE	
✓US 3355046	A	28-11-1967	NONE	
✓US 3804281	A	16-04-1974	NONE	
✓US 2637182	A	05-05-1953	NONE	
US 3355045	A	28-11-1967	NONE	
✓FR 2413286	A	27-07-1979	FR 2413286 A1	27-07-1979
✓GB 2355918	A	09-05-2001	NONE	
✓US 4412644	A	01-11-1983	NONE	
✓US 4832212	A	23-05-1989	NONE	
✓GB 2312611	A	05-11-1997	NONE	